

Claims

1. A self cleaning filter assembly for use in an exhaust system, including:
a casing for placement in the path of an air flow, the casing containing:
5 a first filter;
a second filter;
a barrier for placement adjacent to the casing to prevent a cleaning
fluid from dripping from the first filter and out from the casing; and
a plurality of spray outlets for dispersion of fluid within the casing and onto
10 the filters,
wherein the plurality of spray outlets create droplets of the cleaning fluid of a
size able to combine with droplets of a contaminant to form combined droplets in
the air flow and wherein the first filter and the second filter captures droplets of the
contaminant and droplets from the spray outlets.
15
2. A self cleaning filter assembly as claimed in claim 1, wherein the barrier is a
plurality of louvres that creates openings when the exhaust system is operational.
3. A self cleaning filter assembly as claimed in claim 1, wherein the barrier is
20 slidable into the casing to create an opening when the exhaust system is
operational.
4. A self cleaning filter assembly as claimed in any one of claims 1 to 3,
wherein the barrier includes baffles to retard the air flow.
25
5. A self cleaning filter assembly as claimed in any one of claims 1 to 4,
wherein the barrier includes at least one chamber for the containment of fluid.
6. A self cleaning filter assembly as claimed in claim 5, wherein there is a
30 conduit for fluid drainage in the at least one chamber.

7. A self cleaning filter assembly as claimed in any one of claims 1 to 6, wherein each spray outlet disperses fluid with an arc of between sixty degrees and one hundred eighty degrees.
- 5 8. A self cleaning filter assembly as claimed in claim 7, wherein each spray outlet disperses fluid with an arc of one hundred and ten degrees.
9. A self cleaning filter assembly as claimed in any one of claims 1 to 8, wherein each spray outlet is selected from a group of outlets consisting of: a fan jet spray, and a nozzle.
- 10 10. A self cleaning filter assembly as claimed in any one of claims 1 to 9, wherein the cleaning fluid includes water and a degreaser in a required ratio in the range 1:10 to 1:50.
- 15 11. A self cleaning filter assembly as claimed in any one of claims 1 to 10, wherein the plurality of spray outlets are on an inlet side of a filter selected from the group consisting of: first filter and second filter.
- 20 12. A self cleaning filter assembly as claimed claim 11, wherein the plurality of spray outlets are located at each edge of a filter selected from the group consisting of: first filter and second filter.
- 25 13. A self cleaning filter assembly as claimed in any one of claims 1 to 10, wherein the plurality of spray outlets are located at the middle portion of each side of a filter selected from the group consisting of: first filter and second filter.
- 30 14. A self cleaning filter assembly as claimed in any one of claims 1 to 10, wherein the plurality of spray outlets are located on opposed corners of a filter selected from the group consisting of: first filter and second filter.
15. A self cleaning filter assembly as claimed in any one of claims 1 to 14, wherein the plurality of spray outlets are located within the casing.

16. A self cleaning filter assembly as claimed in any one of claims 1 to 15, wherein the barrier comprises at least one chamber with at least one baffle therein.
- 5 17. A self cleaning filter assembly as claimed in claim 2, wherein the plurality of louvres are fixed in a particular orientation.
18. A circulation system for fluids into at least one self cleaning filter assembly including:
- 10 a circulation tank; and
a circulation pump;
wherein the circulation pump operates as a venturi pump to circulate fluids in the system.
- 15 19. A circulation system as claimed in claim 18, further including at least one valve to control the flow of water into the circulation tank.
20. A circulation system as claimed in either claim 18 or 19, further including a supplementary tank for the containment of a fluid constituent.
- 20 21. A circulation system as claimed in claim 20, further including a dispenser for the fluid constituent.
22. A circulation system as claimed in either claim 20 or 21, wherein the fluid
25 constituent is degreaser.
23. A circulation system as claimed in claims 18 to 22, wherein the fluid is cleaning solution.
- 30 24. A circulation system as claimed in claim 23, wherein the ratio of degreaser to water is in the range of 1:10 to 1:50.

25. A circulation system as claimed in claim 24, wherein the ratio of degreaser to water is 1:20.
26. A circulation system as claimed in any one of claims 18 to 25, wherein a
5 stream of air after the circulation pump is passed into the fluids in the system.
27. A circulation system as claimed in any one of claims 18 to 25, wherein a stream of air before the circulation pump is passed into the fluids in the system.
- 10 28. A circulation system as claimed in any one of claims 18 to 27, wherein the circulation pump includes a filter.
29. A circulation system as claimed in any one of claims 18 to 28, wherein the circulation tank has an inclined sloping base.